

# Smart LED Ceiling Light



# Starry Sky Patent Design



**DALEN**  
Tech for better life


CE PS E Smart Home Residential Lighting  
Smart LED Ceiling Light



Model	DL-C206T
Input Power	38W
Color Temperature	2800K-6000K, 6 Level Adjustable with remote control
Luminous Flux	3600LM, 6 Level Adjustable with remote control
LED Specification	SAMSUNG 5630(120LEDs)
Lamp Size	φ490mm×108mm
Net weight	2.0kg



Model	DL-C406T
Input Power	56W
Color Temperature	2800K-6000K, 10 Level Adjustable with remote control
Luminous Flux	5000LM, 10 Level Adjustable with remote control
LED Specification	SAMSUNG 5630(128LEDs)
Lamp Size	φ600mm×78mm
Net weight	2.8kg



Model	DL-Q50TX / Q50T
Input Power	50W
Color Temperature	2800K-6000K, 6 Level Adjustable with remote control
Luminous Flux	3600LM, 4 Level Adjustable with remote control
LED Specification	SAMSUNG 2835(144LEDs)
Lamp Size	600*600*80mm
Net weight	5.3kg



Model	DL-C102TX / C102T
Input Power	28W
Color Temperature	2800K-6000K, 4 Level Adjustable with remote control
Luminous Flux	2600LM, 4 Level Adjustable with remote control
LED Specification	SAMSUNG 2835(80LEDs)
Lamp Size	φ450mm×91mm
Net weight	1.3kg



Model	DL-C405TS
Input Power	38W
Color Temperature	2800K-6000K, 6 Level Adjustable with remote control
Luminous Flux	3800LM, 6 Level Adjustable with remote control
LED Specification	SAMSUNG 5630(120LEDs)
Lamp Size	φ530mm×120mm
Net weight	1.6kg



Model	DL-C205TX / C205T
Input Power	25W
Color Temperature	2800K-6000K, 4 Level Adjustable with remote control
Luminous Flux	2300LM, 4 Level Adjustable with remote control
LED Specification	SAMSUNG 2835(60LEDs)
Lamp Size	φ350mm×98mm
Net weight	0.8kg




Model	DL-M25T
Input Power	25W
Color Temperature	2800K-6000K, 4 Level Adjustable with remote control
Luminous Flux	2000LM, 4 Level Adjustable with remote control
LED Specification	SAMSUNG 2835(60LEDs)
Lamp Size	φ350mm×98mm
Net weight	1.1kg



Model	DL-S28T / S28TX
Input Power	28W
Color Temperature	2800K-6000K, 4 Level Adjustable with remote control
Luminous Flux	2600LM, 4 Level Adjustable with remote control
LED Specification	SAMSUNG 2835(80LEDs)
Lamp Size	Ø430mm×91mm
Net weight	1.3kg



Model	DL-C28T / C28TX
Input Power	28W
Color Temperature	2800K-6000K, 4 Level Adjustable with remote control
Luminous Flux	2600LM, 4 Level Adjustable with remote control
LED Specification	SAMSUNG 2835(80LEDs)
Lamp Size	φ500mm×91mm
Net weight	1.5kg



Model	DL-C405T / C405TX
Input Power	38W
Color Temperature	2800K-6000K, 6 Level Adjustable with remote control
Luminous Flux	3800LM, 6 Level Adjustable with remote control
LED Specification	SAMSUNG 5630(120LEDs)
Lamp Size	φ530mm×135mm
Net weight	1.9kg



Model	DL-C407T / C407TX
Input Power	38W
Color Temperature	2800K-6000K, 6 Level Adjustable with remote control
Luminous Flux	3800LM, 6 Level Adjustable with remote control
LED Specification	SAMSUNG 5630(120LEDs)
Lamp Size	φ600mm×135mm
Net weight	2.2kg



Model	DL-C309T / C309TX
Input Power	38W
Color Temperature	2800K-6000K, 6 Level Adjustable with remote control
Luminous Flux	3600LM, 6 Level Adjustable with remote control
LED Specification	SAMSUNG 5630(120LEDs)
Lamp Size	φ566mm×108mm
Net weight	2.2kg



Model	DL-C408T / C408TX
Input Power	56W
Color Temperature	2800K-6000K, 10 Level Adjustable with remote control
Luminous Flux	5000LM, 10 Level Adjustable with remote control
LED Specification	SAMSUNG 5630(128LEDs)
Lamp Size	φ600mm×130mm
Net weight	2.8kg





Model	DL-C408T / C408TX
Input Power	56W
Color Temperature	2800K-6000K, 10 Level Adjustable with remote control
Luminous Flux	5000LM, 10 Level Adjustable with remote control
LED Specification	SAMSUNG 5630(128LEDs)
Lamp Size	φ600mm×130mm
Net weight	2.8kg



Authorised Distributor  
**UNIRANGE TRADING**  
41 Tyrwhitt Road  
Singapore 207539  
Tel: +65 6396 3969  
Fax: +65 6251 6419  
Email : [sales@unirange.com](mailto:sales@unirange.com)  
Website : [www.unirange.com](http://www.unirange.com)

Bus Services:  
23, 64, 65, 66, 66A, 130,  
139, 147, 147A



Notes: AC220V±10%;50/60HZ; Life Time:40000H; Eye protection:Yes; Ra>85; Sleep Mode:Yes; Night Light:Yes; Wall Switch Switching Fuction: Yes; Insect resistance:Yes.

Dalen Singapore Pte. Ltd.

DALEN Global: China | Japan | Singapore | Italy | Benelux | Czech | United Kingdom



## Intelligent eco LED Ceiling Light

Comfortable Lighting Atmosphere and Real Eye-protecting Technology

The innovative functions and advantages of DALEN Smart LED Ceiling lights are with unique positioning of cool white and warm white LED chips to achieve uniform dimmable & CCT lighting performance, double insurance of eye protection without ripple wave flickering & blue light extravasation, excellent lm/w insect resistant, easy installation, dynamic energy saving and above 10 years long life time.

### Whole Light Neutral White, the brightest light



### Cool White Fresh & Cool light



### Dimmable

6 Level Brightness adjustable by remote control.

### Glare-free

Dimming to 90% of the brightness in half an hour, dynamic energy-saving and eye-protecting.



### Warm White Leisure and Warm light



### Night Light Only 1W power consumption





### Sleep mode Help you fall asleep easily




### Channel Switch one remote can control several lights


Press the CH1/CH2 button for more than 3 seconds to change the channel and control the matching lights. (25/28/50W series non-supported.)



### Uniform Lighting Performance




### Excellent Luminous Efficacy



### Fabulous Color-Rending



### Insect Resistance



Digital plus analog dimming scheme, high efficiency and stable, with RUBYCON or SAMYOUNG long life time electrolytic capacitors.

### Double insurance of Eye-protection

#### No ripple wave flickering

When using a phone with camera viewfinder watching the lamp at about 15cm distance, almost no ripple wave flickering & PF>0.9, excellent invisible care of the family, really eye-protection.



#### LED blue light suppression


EN62471 Approved

Notice: ripple wave flickering will lead to asthenopia and myopic eye, and blue light extravasation may even go through the retina and cause irreversible injury to people's especially Children's eyes.



### Wall Switch Switching Function

If wall switch is turned off & on within 2 seconds continuously, lighting states will be changed between three modes - Whole Light, Warm White & Night Light, so that people can also switch the commonly used lighting modes without using remote control.



### Easy installation



Note: Above installation is for 38/56W series.