



LED Down Light-Premium



- LED edge-lit technology, uniform light, ultra-thin design (2-5cm), easy to use in narrow space.
- Narrow frame to increase wider emitting area.
- Ideal replacement for traditional 26W CFL down light or.
- Energy-saving, eco-friendly for the environment.



6-inch Down Light (ED060-12YR)
won 22th Taiwan Excellence Award (2014)



CRI : 80 ; Color Temperature : 5000K (4450K-5150K) / 4000K (3500K-4150K) / 3000K (2750K-3150K)

Model		ED060-xxYR-1				
Dimension	Φ 186 x 47 mm (6")		Φ 186 x 19 mm (6")			
Power Consumption	18 w		12 w			
Color Temperature	5000K	4000K / 3000K		5000K	4000K / 3000K	
Lumious Flux	1060 lm	1040 lm		740 lm	720 lm	
Illumination (1m)	360 lux	350 lux		240 lux	230 lux	
Illumination (2m)	105 lux	100 lux		75 lux	70 lux	
Power Factor	PF > 0.9					
Model		ED050-xxYR-1			ED040-xxYR-1	
Dimension	Φ 156 x 38 mm (5")			Φ 132 x 29 mm (4")		
Power Consumption	18 w		12 w		11.6 w	
Color Temperature	5000K / 4000K	3000K	5000K / 4000K	3000K	5000K / 4000K	3000K
Lumious Flux	1290 lm	1180 lm	860 lm	780 lm	855 lm	780 lm
Illumination (1m)	480 lux	440 lux	300 lux	280 lux	320 lux	300 lux
Illumination (2m)	120 lux	110 lux	75 lux	70 lux	80 lux	75 lux
Power Factor	PF > 0.9					

- xx indicates power consumption of luminaire ; Y indicates Color Temperature of luminaire, B:3000K; D:4000K; F:5000K; J:5300K; G:5700K
- The above specification is the standard value, the company reserves the right to information revise.